MAXCLEANER





Removing old joints



Effective for large areas



Does not require wate



Does not require shielding



Safe for cars and pedestrians

Effective joint cleaner that quickly and safely blows away joints, debris, moss, and weeds without hitting passersby. The joint depth can be adjusted to ensure an even joint depth.









Technical data

Size & Weight
Length: 75 cm
Width: 36 cm
Height: 10 cm
Weight: 25 kg

Air flow &
Connection
4 m3/min. 5-7 bar
We recommend a
compressor with
variable air pressure.

2 x 3/4" connection

Colour

How-to guide



Connect MaxCleaner with a compressor of approximately 4 m3/min, 5-7 bar, preferably with variable air pressure.

Run MaxCleaner over the old pavement to remove loose sand to an even joint depth. The loose sand falls out to the left side of the machine when the left flap is opened. The cleaned material is easily removed with a broom.

Remove any rooted weeds if necessary.

MaxCleaner easily removes moss and smaller growth, but not deeply rooted vegetation.

All root systems should be removed before jointing.

Run MaxCleaner over the pavement one final time. Sweep afterwards. You are now ready to grout.

Remember protective gear.
Always tighten the nozzles (on the underside of the machine) every 10 hours.





Please contact us for counselling during over opening hours

Lervejdal 14D • Addit • DK-8740 Brædstrup
Phone: +45 8622 1122 • info@lithomex.com • VAT no.: 37 39 48 74